

FLUID SPECIFICATIONS (U.S. only) 2010-2013 MY

Lexus

Vehicle Model	Engine Type	Engine Oil (Drain & Refill w/Filter Change)				Coolant <i>Toyota Super Long Life Coolant (SLLC)</i>	Manual Transmission	Automatic Transmission	Transfer Case	Front and Rear Differential
		2010	2011	2012	2013					
CT200h	2ZR-FXE		0W-20 4.4qts (4.2 liters)	0W-20 4.4qts (4.2 liters)	0W-20 4.4qts (4.2 liters)	Gas Engine SLLC w/Exhaust Heat Recirculation: 7.3qts (6.9 liters) w/o Exhaust Heat Recirculation: 6.9qts (6.5 liters) Power Control Unit: 2.2qts (2.1 liters)		ATF WS*		
ES350	2GR-FE	5W-30 6.4qts (6.1 liters)	5W-30 6.4qts (6.1 liters)	5W-30 6.4qts (6.1 liters)	0W-20 6.4qts (6.1 liters)	9.5qts (9.0 liters) SLLC		ATF WS*		
GS350	2GR-FSE	5W-30 6.7qts (6.4 liters)	5W-30 6.7qts (6.4 liters)		0W-20 6.3 qts (6 liters)	9.6qts (9.1 liters) SLLC (Thru 2012MY) 10.3 qts (9.7 liters) SLLC (2013MY)		ATF WS*		Front: Hypoid API (GL-5 SAE 90) ³ ; API (GL-5 SAE 80 or 80W-90) ⁴ Rear: LT 75W-85 GL-5
GS450h	2GR-FSE	5W-30 6.7qts (6.3 liters)	5W-30 6.7qts (6.3 liters)			Gas Engine: 9.8qts (9.3 liters) SLLC Power Control Unit: 3.0qts (2.9 liters)		ATF WS*		LT 75W-85 GL-5
	2GR-FXE				0W-20 6.2qts (5.9 liters)	Gas Engine: 9.9qts (9.4 liters) SLLC Power Control Unit: 3.3qts (3.1 liters)		ATF WS*		LT 75W-85 GL-5
GS460	1UR-FSE	0W-20 ⁹ 5W-20 9.1qts (8.6 liters)	0W-20 ⁹ 5W-20 9.1qts (8.6 liters)			11.7qts (11.0 liters) SLLC		ATF WS*		LT 75W-85 GL-5
GX460	1UR-FSE	0W-20 8.2qts (7.8 liters)	0W-20 8.2qts (7.8 liters)	0W-20 8.2qts (7.8 liters)	0W-20 8.2qts (7.8 liters)	16.3qts (15.4 liters) SLLC w/ rear heater 14.5qts (13.7 liters) SLLC w/o rear heater		ATF WS*	LF SAE 75W	LT 75W-85 GL-5
HS250h	2AZ-FXE	0W-20 4.5qts (4.3 liters)	0W-20 4.5qts (4.3 liters)	0W-20 4.5qts (4.3 liters)		Gas Engine: 7.7qts (7.3 liters) SLLC Power Control Unit: 3.1qts (2.9 liters)		ATF WS*		
IS250	4GR-FSE	5W-30 2WD: 6.6qts (6.3 liters) 4WD: 6.8qts (6.5 liters)	0W-20 2WD: 6.6qts (6.3 liters) 4WD: 6.8qts (6.5 liters)	0W-20 2WD: 6.6qts (6.3 liters) 4WD: 6.8qts (6.5 liters)	0W-20 2WD: 6.6qts (6.3 liters) 4WD: 6.8qts (6.5 liters)	10.9qts (10.3 liters) SLLC	API GL-5 75W-90	ATF WS*	ATF WS*	Rear: LT 75W-85 GL-5 Front: API GL-5 (SAE 90) ³ ; API GL-5 (SAE 80 or 80W-90) ⁴
IS250C	4GR-FSE	5W-30 2WD: 6.6qts (6.3 liters) AWD: 6.8qts (6.5 liters)	0W-20 2WD: 6.6qts (6.3 liters) AWD: 6.8qts (6.5 liters)	0W-20 2WD: 6.6qts (6.3 liters) AWD: 6.8qts (6.5 liters)	0W-20 2WD: 6.6qts (6.3 liters) AWD: 6.8qts (6.5 liters)	10.9 qts (10.3 liters) SLLC	API GL-5 75W-90	ATF WS		LT 75W-85 GL-5
IS350	2GR-FSE	5W-30 6.7qts (6.4 liters)	5W-30 6.7qts (6.4 liters)	5W-30 6.7qts (6.4 liters)	5W-30 6.7qts (6.4 liters)	9.6qts (9.1 liters) SLLC		ATF WS*		LT 75W-85 GL-5
IS350C	2GR-FSE	5W-30 6.7qts (6.4 liters)	5W-30 6.7qts (6.4 liters)	5W-30 6.7qts (6.4 liters)	5W-30 6.7qts (6.4 liters)	10.9 qts (10.3 liters) SLLC		ATF WS*		LT 75W-85 GL-5
ISF	2UR-GSE	5W-30 9.8qts (9.3 liters)	5W-30 9.8qts (9.3 liters)	5W-30 9.8qts (9.3 liters)	5W-30 ⁹ 10W-30 9.8qts (9.3 liters)	12.6qts (11.9 liters) SLLC		ATF WS*		LT 75W-85 GL-5
LFA	1LR-GUE			5W-50 Single Oil Cooler: 16.9 qts (16 liters) Twin Oil Cooler: 18 qts (17 liters)						
LS460	1UR-FSE	0W-20 ⁹ 5W-20 2WD: 9.1qts (8.6 liters) AWD: 9.5qts (9.0 liters)	0W-20 ⁹ 5W-20 2WD: 9.1qts (8.6 liters) AWD: 9.5qts (9.0 liters)	0W-20 ⁹ 5W-20 2WD: 9.1qts (8.6 liters) AWD: 9.5qts (9.0 liters)	0W-20 ⁹ 5W-20 2WD: 9.1qts (8.6 liters) AWD: 9.5qts (9.0 liters)	SLLC 2WD 11.6 qts (11.0 liters) AWD 11.7 qts (11.1 liters)		ATF WS*	Transfer gear oil LL80 LX SAE 75W-85 GL-5	Front/Rear: LT 75W-85 GL-5 Rear: (AWD) LX 75W-85 GL-5

¹ Above 40°F² Below 40°F³ Above 0°F⁴ Below 0°F

* Refer to the ATF adjustment procedure in the RM
© 2012 Toyota Motor Sales, USA

⁵w/twg pkg⁶w/o twg pkg⁹Best choice for fuel economy and cold starting

FLUID SPECIFICATIONS (U.S. only) 2010-2013 MY

Lexus

Vehicle Model	Engine Type	Engine Oil (Drain & Refill w/Filter Change)				Coolant <i>Toyota Super Long Life Coolant (SLLC)</i>	Manual Transmission	Automatic Transmission	Transfer Case	Front and Rear Differential
		2010	2011	2012	2013					
LS600h	2UR-FSE	0W-20 ¹ 5W-20 9.5qts (9.0 liters)	0W-20 ² 5W-20 9.5qts (9.0 liters)	0W-20 ³ 5W-20 9.5qts (9.0 liters)		SLLC Gas Engine: 11.7qts (11.1 liters) Power Control Unit: 2.7qts (2.6 liters)		ATF WS*	Transfer gear oil LL80 LX SAE 75W-85 GL-5	Front: LT 75W-85 GL-5 Rear: LX 75W-85 GL-5
LX570	3UR-FE	0W-20 ⁴ 5W-20 Blue Dipstick 7.4qts. Green Dipstick 7.9qts.	0W-20 ⁵ 5W-20 7.9qts (7.5 liters)		0W-20 ⁶ 5W-20 7.9qts (7.5 liters)	17.6qts (16.7 liters) SLLC		ATF WS*	API GL-5 75W	LT 75W-85 GL-5
RX350	2GR-FE	0W-20 6.4qt. (6.1 liters)	0W-20 6.4qts (6.1 liters)	0W-20 6.4qts (6.1 liters)	0W-20 6.4qts (6.1 liters)	SLLC 9.0qts (8.5 liters) ⁶ 10.0qts (9.5 liters) ⁵		ATF WS*	LT 75W-85 GL-5	LT 75W-85 GL-5
RX450h	2GR-FXE	0W-20 6.4qts (6.1 liters)	0W-20 6.4qts (6.1 liters)	0W-20 6.4qts (6.1 liters)	0W-20 6.4qts (6.1 liters)	SLLC 12.1qts (11.4 liters) ⁶ 12.4qts (11.7 liters) ³ Power Control Unit: 2.0qts (1.9 liters)		ATF WS*		
SC430	3UZ-FE	5W-30 5.5qts (5.2 liters)				10.5qts (9.9 liters) SLLC		ATF WS*		LT 75W-85 GL-5

¹ Above 40°F

² Below 40°F

³ Above 0°F

⁴ Below 0°F

* Refer to the ATF adjustment procedure in the RM
© 2012 Toyota Motor Sales, USA

⁵w/twg pkg

⁶w/o twg pkg

⁹Best choice for fuel economy and cold starting